



## Features

- Fully heat treated
- Dual ball bearing raceways
- High luster chrome or black zinc finish
- Matching thread guards
- Precision ball bearing wheels for excellent rollability
- Choice of new vipor wheel (85-90A) or soft neoprene rubber (50-60A) durometer

## Applications

- Medical Equipment
- Electronic Equipment
- Seating

## Options

**Brakes:** Tread brake uniformly integrated into body design for smooth look and ease of activation 3" models only.

### Bolt-In Stems:

A variety of stems can be attached to the kingpinless fastening #403 providing the ultimate in versatility. Contact factory for bolt-in stem part numbers.



**Black zinc** finish is available with the **vipor** wheel for a minimum purchase (Consult factory).

## Finish Selection



Bright Chrome



Black Zinc



Soft Neoprene Rubber



Vipor

## Wheel Selection



### Tread Brake

Add [B] at end of model. Swivel radius is 3-1/8".

## Hollow Kingpin Models (7/16": Recommended mounting bolt 3/8" diameter - 16 x 1/2" minimum)

Wheel Dia.	Tread Width	Tread Type	Finish	Bearing Type	Dynamic Load	Mounting Height	Swivel Radius	Part Number	Fastening Selection
<b>3"</b>	15/16"	Neoprene	Bright Chrome	Precision	110 lbs	3-7/8"	2-7/8"	POM30403BC-NPR	403
	15/16"	Neoprene	Black Zinc	Precision	110 lbs	3-7/8"	2-7/8"	POM30403BZ-NPR	403
	15/16"	Vipor	Bright Chrome	Precision	120 lbs	3-7/8"	2-7/8"	POM30403BC-VPR33(CK)	403

## Threaded Stem Models


Wheel Dia.	Tread Width	Tread Type	Finish	Bearing Type	Dynamic Load	Mounting Height	Swivel Radius	Part Number	Fastening Selection
<b>3"</b>	15/16"	Neoprene	Bright Chrome	Precision	110	3-7/8"	2-7/8"	POM30__BC-NPR	All below
	15/16"	Neoprene	Black Zinc	Precision	110	3-7/8"	2-7/8"	POM30__BZ-NPR	All below
	15/16"	Vipor	Bright Chrome	Precision	120	3-7/8"	2-7/8"	POM30__BC-VPR33(CK)	All below

507

605

637

748



To order include fastener code.  
Example: POM30**507**BC-NPR33(KK)



### Tread Brake

Add [B] at end of model. Swivel radius is 3-1/8"