Pilot Unhooded Die-Cast Twin Wheel

....

1-800-215-8220

Features

· Zinc die-cast body

Applications

- Seating
- Concealed axle
 Electronic Equipment
 - Store Fixtures

Options

Fasteners: Stemless, threaded stem, grip ring stem, grip neck stem, plate.

Urethane Wheel: To order, insert [-U] at the end of the Part Number.



shophord

Stemless Models											
Wheel Diameter	Tread Material	Finish	Dynamic Load	Mounting Height	Swivel Radius	Part Number	Fastening Selection				
50mm	Nylon	Flat Black	75 lbs	N/A	1-11/16"	PPB50000FB	000				
60mm	Nylon	Flat Black	100 lbs	N/A	2-1/16"	PPB60000FB	000				



Threaded Stem Models										
Wheel Diameter	Tread Material	Finish	Dynamic Load	Mounting Height	Swivel Radius	Part Number	Fastening Selection			
50mm	Nylon	Flat Black	75 lbs	2-1/2"	1-11/16"	PPB50FB	828, 525, 507, 639, 637, 605			
60mm	Nylon	Flat Black	100 lbs	2-7/8"	2-1/16"	PPB60FB	525, 545, 526, 639, 637, 605			
	828 - 5/8"↓ 1/4" 639 - 5/8"↓ 3/8"	5/16 637	UNC12		1-1/4 0"	526 → UNC18 5/16"	To order include fastener code. Example: PPB60 526 FB.			