



Softech Soft Tread Twin Wheel Casters



Features

- Soft 70-75/A durometer tread constructed of high-tech thermoplastic elastomer
- High load ratings
- Quiet mobility

Applications

- Electronic Equipment
- Medical Equipment
- Audio/Visual Equipment
- Furniture

Options

Fasteners: Threaded, Top Plate, Grip Ring, Grip Neck
Brake: To order insert [-B] at the end of the Part Number.



Threaded Stem Models (Black)

Wheel Diameter	Tread Material	Dynamic Load	Mounting Height	Swivel Radius	Part Number	Fastening Selection
3" 75mm	Thermoplastic Elastomer	165	3-1/4"	2-1/2"	PSF75__BK	507, 637, 634, 741, 748
4" 100mm	Thermoplastic Elastomer	225	4-3/8"	3-5/8"	PSF100__BK	637, 634, 741, 748
5" 125mm	Thermoplastic Elastomer	225	5-7/16"	4-1/2"	PSF125__BK	741, 748

For brake add [-B] to end of part number.
3" dia. swivel radius is 3-3/16", 4" dia. is 4-1/2", 5" dia. is 5-1/8"




To order include fastener code.
Example: (PSF75507BK).



Threaded Stem Models (Grey)

Wheel Diameter	Tread Material	Dynamic Load	Mounting Height	Swivel Radius	Part Number	Fastening Selection
3" 75mm	Thermoplastic Elastomer	165	3-1/4"	2-1/2"	PSF75__GR	507, 637, 634, 741, 748
4" 100mm	Thermoplastic Elastomer	225	4-3/8"	3-5/8"	PSF100__GR	637, 634, 741, 748
5" 125mm	Thermoplastic Elastomer	225	5-7/16"	4-1/2"	PSF125__GR	741, 748

For brake add [-B] to end of part number.
3" dia. swivel radius is 3-3/16", 4" dia. is 4-1/2", 5" dia. is 5-1/8"



To order include fastener code.
Example: (PSF75507GR).

